Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-983-7948

| Reliability Indic | ator: |
|--------------------|--|
| Not established | |
| Overall Length: | |
| Any acceptable | |
| Tempurature Ra | ating: |
| -55.0 degrees ce | elsius and 135.0 degrees celsius |
| Environmental | Protection: |
| Corrosion resista | ant and flame resistant and mildew resistant and water resistant |
| Expanded Insid | le Diameter: |
| 0.046 inches | |
| Recovered Insi | de Diameter: |
| 0.023 inches | |
| Recovered Wal | I Thickness: |
| Between 0.013 i | nches and 0.019 inches |
| Heat Shrinkage | Rating In Percent: |
| 50.0 | |
| Min. Tensile Str | rength (psi): |
| 1500 pounds pe | r square inch |
| Flexibility: | |
| Flexible | |
| Color: | |
| Brown | |
| Material: | |
| Plastic, polyolef | in, mil-i-23053/5, class 1 |
| Material: | |
| Plastic cross-link | ked polyolefin |
| Style Designate | pr: |
| Shrinkable | |
| Dielectric Mater | rial Voltage Rating Per Unit Thickness: |
| 500.0 volts per n | nilitary /0.001 inch/ |
| Shelf Life: | |
| N/a | |
| Unit Of Measure | e: |
| | |
| Demilitarization | 1: |
| No | |
| Fiig: | |
| A22500 | |