Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-00-995-4565

### Wall Thickness:

Between 0.013 inches and 0.019 inches

### **Reliability Indicator:**

Not established

# **Inside Diameter:**

Between 0.032 inches and 0.039 inches

# **Overall Length:**

Any acceptable

### **Tempurature Rating:**

-10.0 degrees celsius and 105.0 degrees celsius

# **Environmental Protection:**

Flame resistant and mildew resistant and oil resistant and heat resistant

# Min. Tensile Strength (psi):

1800 pounds per square inch

#### Flexibility:

Flexible

# Color:

Black

# Material:

Plastic, polyvinyl chloride, mil-i-631, type f, form u, subform ua, grade c, class 1, category 1

# Material:

Plastic polyvinyl chloride

### Style Designator:

Nonshrinkable

# **Dielectric Material Voltage Rating Per Unit Thickness:**

800.0 volts per military /0.001 inch/

# **Specification Or Standard:**

1 category and 1 class and u form and c grade and 20 awg size and ua subform and f type

# **Departure From Cited Document:**

As mod by color

#### Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

# Fiig:

A22500

# Mil-std (military Standard):

Mil-i-631 spec.