NSN 5970-00-998-2222

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-00-998-2222 **Reliability Indicator:** Not established **Tempurature Rating:** -55.0 degrees celsius **Environmental Protection:** Flame resistant and mildew resistant and solvent resistant and water resistant Main Body Inside Diameter: 1.520 inches as supplied **First Branch Inside Diameter:** 1.060 inches as supplied **Second Branch Inside Diameter:** 1.060 inches as supplied **Distance From Intersecting Centerline Of Main Body To End Of First Branch:** 3.220 inches after unrestricted recovery Main Body Wall Thickness: 0.120 inches after unrestricted recovery First Branch Wall Thickness: 0.100 inches after unrestricted recovery **Second Branch Wall Thickness:** 0.100 inches after unrestricted recovery **Distance From Edge Of Main Body To Intersecting Centerlines:** 2.580 inches after unrestricted recovery Angle Between Main Body And Second Branch Centerlines In Deg: 22.5 after unrestricted recovery Min. Tensile Strength (psi): 1500 pounds per square inch **Special Features:** Adhesive coating Flexibility: Flexible Color: Black Material: Rubber, neoprene, rt-501, raychem corp Material: Rubber, neoprene, rt-501, raychem corp **Style Designator:** Transition-y **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/

Shelf Life:

N/a

NSN 5970-00-998-2222

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A22500