

View Online at <https://aerobasegroup.com/nsn/5970-00-998-2224>

**Dielectric Withstanding Voltage In Volts:**

200.0

**Reliability Indicator:**

Not established

**Tempurature Rating:**

-55.0 degrees celsius and 150.0 degrees celsius

**Environmental Protection:**

Any acceptable

**Main Body Inside Diameter:**

1.120 inches as supplied

**First Branch Inside Diameter:**

1.060 inches as supplied

**Second Branch Inside Diameter:**

1.060 inches as supplied

**Distance From Intersecting Centerline Of Main Body To End Of First Branch:**

3.320 inches after unrestricted recovery

**Main Body Wall Thickness:**

0.100 inches after unrestricted recovery

**First Branch Wall Thickness:**

0.100 inches after unrestricted recovery

**Second Branch Wall Thickness:**

0.100 inches after unrestricted recovery

**Distance From Edge Of Main Body To Intersecting Centerlines:**

3.420 inches after unrestricted recovery

**Angle Between Main Body And Second Branch Centerlines In Deg:**

22.5 after unrestricted recovery

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Flexibility:**

Flexible

**Color:**

Black

**Material:**

Rubber, chloroprene

**Material:**

Rubber chloroprene class cr

**Style Designator:**

Transition-y

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500