

View Online at <https://aerobasegroup.com/nsn/5970-01-003-7640>

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

First Branch Inside Diameter:

0.130 inches after unrestricted recovery

Second Branch Inside Diameter:

0.130 inches after unrestricted recovery

Third Branch Inside Diameter:

0.130 inches after unrestricted recovery

Fourth Branch Inside Diameter:

0.130 inches after unrestricted recovery

First Branch Wall Thickness:

0.050 inches after unrestricted recovery

Second Branch Wall Thickness:

0.050 inches after unrestricted recovery

Third Branch Wall Thickness:

0.050 inches after unrestricted recovery

Fourth Branch Wall Thickness:

0.050 inches after unrestricted recovery

Main Bodylength:

2.090 inches after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, polyolefin, rt-301, raychem corp

Material:

Plastic, polyolefin, rt-301, raychem corp

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500