

View Online at <https://aerobasegroup.com/nsn/5970-01-004-6355>

**Dielectric Withstanding Voltage In Volts:**

500.0

**Reliability Indicator:**

Not established

**Overall Length:**

Any acceptable

**Temperature Rating:**

-55.0 degrees celsius and 135.0 degrees celsius

**Coating Material:**

Any acceptable

**Environmental Protection:**

Corrosion resistant and water resistant and high temp

**Expanded Inside Diameter:**

0.187 inches

**Recovered Inside Diameter:**

0.093 inches

**Recovered Wall Thickness:**

0.020 inches

**Heat Shrinkage Rating In Percent:**

50.0

**Impregnation Material:**

Any acceptable

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Flexibility:**

Flexible

**Color:**

Clear

**Material:**

Plastic, polyolefin, mil-i-23053/5, class 2

**Style Designator:**

Shrinkable

**Test Data Document:**

81349-mili23053 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Or Standard:**

2 class

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500