Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-013-5840

| View Online at https://aerobasegroup.com/nsn/5970-01-013-5840  |
|--|
| Tempurature Rating:  |
| -55.0 degrees celsius  |
| Environmental Protection:  |
| Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant |
| Main Body Wall Thickness:  |
| 0.070 inches after unrestricted recovery   |
| Main Bodylength:   |
| 2.160 inches after unrestricted recovery   |
| Main Body Small End Inside Diameter:   |
| 1.120 inches as supplied   |
| Main Body Large End Inside Diameter:   |
| 1.120 inches as supplied   |
| Distance From Bottom Of Shoulder To Large End Of Main Body:  |
| 1.090 inches after unrestricted recovery   |
| Distance From Top Of Shoulder To Small End Of Main Body:   |
| 0.650 inches after unrestricted recovery   |
| Min. Tensile Strength (psi):   |
| 1500 pounds per square inch  |
| Special Features:  |
| Large end has lip and circular ridge inside  |
| Flexibility:   |
| Semirigid  |
| Color:   |
| Black  |
| Material:  |
| Plastic, polyolefin, rt-301, raychem corp  |
| Material:  |
| Plastic, polyolefin, rt-301, raychem corp  |
| Style Designator:  |
| Boot-straight  |
| Dielectric Material Voltage Rating Per Unit Thickness:   |
| 200.0 volts per military /0.001 inch/  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A22500   |
|  |