# NSN 5970-01-019-3256

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-019-3256

#### **Tempurature Rating:**

-55.0 degrees celsius

#### **Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

#### Large End Wall Thickness Of Main Body:

0.080 inches after unrestricted recovery

#### Small End Wall Thickness Of Main Body:

0.045 inches after unrestricted recovery

#### Main Bodylength:

Any acceptable as supplied

#### Main Body Small End Inside Diameter:

1.470 inches as supplied

#### Main Body Large End Inside Diameter:

1.470 inches as supplied

#### Distance From Top Of Shoulder To Small End Of Main Body:

5.660 inches after unrestricted recovery

#### **End Largest Diameter:**

1.150 inches after unrestricted recovery

# Min. Tensile Strength (psi):

1200 pounds per square inch

# Lip Height:

0.120 inches after unrestricted recovery

#### Lip Width:

0.065 inches after unrestricted recovery

#### **Special Features:**

Inside surface coated with adhesive

# Flexibility:

Flexible

# Height:

0.840 inches as supplied

#### Color:

Black

### Material:

Plastic, polyolefin, rt-1304, raychem corporation or plastic, polyolefin, mpf-666, 3m co

#### Material:

Plastic, polyolefin, rt-1304, raychem corporation or plastic, polyolefin, mpf-666, 3m co

### **Style Designator:**

Boot-90 degrees

# **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

# Shelf Life:

N/a

# NSN 5970-01-019-3256

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A22500