NSN 5970-01-020-3418

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-020-3418

~		e Rating:
ıαm	MIII MATIII	a Patina.
ICIII	Dui atui	c ivaliiiu.

-65.0 degrees celsius and 136.0 degrees celsius

Environmental Protection:

Corrosion resistant and oil resistant and ozone resistant and solvent resistant and water resistant

Main Body Inside Diameter:

1.250 inches as supplied

First Branch Inside Diameter:

0.500 inches as supplied

Second Branch Inside Diameter:

0.500 inches as supplied

Third Branch Inside Diameter:

0.500 inches as supplied

Fourth Branch Inside Diameter:

0.500 inches as supplied

Main Body Wall Thickness:

0.090 inches after unrestricted recovery

First Branch Wall Thickness:

0.090 inches after unrestricted recovery

Second Branch Wall Thickness:

0.090 inches after unrestricted recovery

Third Branch Wall Thickness:

0.090 inches after unrestricted recovery

Fourth Branch Wall Thickness:

0.090 inches after unrestricted recovery

Min. Tensile Strength (psi):

1000 pounds per square inch

Special Features:

Supplied with sealant

Flexibility:

Flexible

Color:

Black

Material:

Plastic, polyolefin

Material:

Plastic polyolefin

Dielectric Material Voltage Rating Per Unit Thickness:

275.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5970-01-020-3418

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500