NSN 5970-01-020-6616

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-020-6616

T	m	nı	ırat	ure	Ra	tin	u.
15	71 I I	υu	ıιαι	uie	I\a		u.

-55.0 degrees celsius and 225.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Main Body Wall Thickness:

0.130 inches after unrestricted recovery

Main Bodylength:

5.130 inches after unrestricted recovery

Main Body Small End Inside Diameter:

2.040 inches as supplied

Main Body Large End Inside Diameter:

2.040 inches as supplied

Distance From Bottom Of Shoulder To Large End Of Main Body:

2.550 inches after unrestricted recovery

Distance From Top Of Shoulder To Small End Of Main Body:

1.650 inches after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

Includes two molding ports 0.180 in. Diameter and 0.120 in. Dia; inside coated with s-1017 adhesive

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mpp-262, 3m co

Material:

Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mpp-262, 3m co

Style Designator:

Boot-straight

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A22500