Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-020-6616

view Online at https://aerobasegroup.com/nsi//3970-01-020-0010	
Tempurature Rating:	
-55.0 degrees celsius and 225.0 degrees celsius	
Environmental Protection:	
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant	:
Main Body Wall Thickness:	
0.130 inches after unrestricted recovery	
Main Bodylength:	
5.130 inches after unrestricted recovery	
Main Body Small End Inside Diameter:	
2.040 inches as supplied	
Main Body Large End Inside Diameter:	
2.040 inches as supplied	
Distance From Bottom Of Shoulder To Large End Of Main Body:	
2.550 inches after unrestricted recovery	
Distance From Top Of Shoulder To Small End Of Main Body:	
1.650 inches after unrestricted recovery	
Min. Tensile Strength (psi):	
1500 pounds per square inch	
Special Features:	
Includes two molding ports 0.180 in. Diameter and 0.120 in. Dia; inside coated with s-1017 adhesive	
Flexibility:	
Semirigid	
Color:	
Black	
Material:	
Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mpp-262, 3m co	
Material:	
Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mpp-262, 3m co	
Style Designator:	
Boot-straight	
Dielectric Material Voltage Rating Per Unit Thickness:	
200.0 volts per military /0.001 inch/	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A22500	