# NSN 5970-01-022-3943

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-022-3943

# **Tempurature Rating:**

-55.0 degrees celsius and 225.0 degrees celsius

#### **Environmental Protection:**

Flame resistant and mildew resistant and solvent resistant

# **Main Body Inside Diameter:**

1.200 inches as supplied

#### First Branch Inside Diameter:

0.800 inches as supplied

# Distance From Intersecting Centerline Of Main Body To End Of First Branch:

Any acceptable as supplied

### Main Body Wall Thickness:

Any acceptable as supplied

#### **First Branch Wall Thickness:**

Any acceptable as supplied

# **Distance From Edge Of Main Body To Intersecting Centerlines:**

Any acceptable as supplied

# Main Bodylength:

Any acceptable as supplied

# Angle Between Main Body And First Branch Centerlines In Deg:

Any acceptable as supplied

# Min. Tensile Strength (psi):

1200 pounds per square inch

#### **Special Features:**

Includes two molding ports

# Flexibility:

Semirigid

# Color:

Black

#### Material:

Plastic, polyolefin, rt-301, raychem corp

#### Material:

Plastic, polyolefin, rt-301, raychem corp

# **Style Designator:**

Transition-45 degrees

# **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

# Shelf Life:

N/a

# **Unit Of Measure:**

--

#### **Demilitarization:**

No

# NSN 5970-01-022-3943

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500