# NSN 5970-01-025-4002

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-025-4002

#### **Tempurature Rating:**

-55.0 degrees celsius and 135.0 degrees celsius

#### **Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and water resistant

#### Large End Wall Thickness Of Main Body:

0.080 inches after unrestricted recovery

#### Small End Wall Thickness Of Main Body:

0.045 inches after unrestricted recovery

#### Main Bodylength:

8.410 inches after unrestricted recovery

#### Main Body Small End Inside Diameter:

1.720 inches as supplied

#### Main Body Large End Inside Diameter:

1.720 inches as supplied

#### Distance From Top Of Shoulder To Small End Of Main Body:

7.128 inches after unrestricted recovery

#### **End Largest Diameter:**

1.532 inches after unrestricted recovery

## Min. Tensile Strength (psi):

1200 pounds per square inch

## Lip Height:

0.120 inches after unrestricted recovery

#### Lip Width:

0.065 inches after unrestricted recovery

#### **Special Features:**

Red color stripe; drain holes included

# Flexibility:

Flexible

# Height:

1.080 inches after unrestricted recovery

#### Color:

Black

#### Material:

Plastic, polyolefin, mil-i-81765/1, type ii

#### Material:

Plastic, polyolefin, mil-i-81765/1, type ii

#### **Style Designator:**

Boot-90 degrees

## **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

# Shelf Life:

N/a

# NSN 5970-01-025-4002

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



nıt	<i>(</i> )+	Measure:

--

Demilitarization:

No

Fiig:

A22500