Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-028-6789

Reliability Indicator:
Not established
Tempurature Rating:
-55.0 degrees celsius and 135.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and water resistant
Main Body Wall Thickness:
0.070 inches after unrestricted recovery
Main Bodylength:
1.500 inches after unrestricted recovery
Main Body Small End Inside Diameter:
0.920 inches as supplied
Main Body Large End Inside Diameter:
0.920 inches as supplied
Distance From Bottom Of Shoulder To Large End Of Main Body:
0.830 inches after unrestricted recovery
Min. Tensile Strength (psi):
1200 pounds per square inch
Special Features:
Red color stripe; inside surface coated with adhesive
Flexibility:
Flexible
Color:
Black
Material:
Plastic, polyolefin, mil-i-81765/1, type ii
Material:
Plastic, polyolefin, mil-i-81765/1, type ii
Style Designator:
Boot-straight
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A22500