

View Online at <https://aerobasegroup.com/nsn/5970-01-032-3556>

**Reliability Indicator:**

Not established

**Tempurature Rating:**

-55.0 degrees celsius and 225.0 degrees celsius

**Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

**Large End Wall Thickness Of Main Body:**

0.070 inches after unrestricted recovery

**Small End Wall Thickness Of Main Body:**

0.032 inches after unrestricted recovery

**Distance From Intersecting Centerlines To Edge Of Small End:**

1.810 inches after unrestricted recovery

**Distance From Centerline Of Small End To Edge Of Large End:**

1.020 inches after unrestricted recovery

**Main Body Small End Inside Diameter:**

1.420 inches as supplied

**Main Body Large End Inside Diameter:**

1.420 inches as supplied

**Distance From Top Of Shoulder To Small End Of Main Body:**

0.590 inches after unrestricted recovery

**Angle Between Large End And Small End Centerlines In Deg:**

90.0 after unrestricted recovery

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Special Features:**

Large end has lip; tab with 0.080 in. Diameter hole on outer wall angle

**Flexibility:**

Semirigid

**Height:**

1.500 inches after unrestricted recovery

**Color:**

Black

**Material:**

Plastic, polyolefin, rt-301, raychem corp

**Material:**

Plastic, polyolefin, rt-301, raychem corp

**Style Designator:**

Boot-90 degrees

**Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500