NSN 5970-01-033-1652

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-033-1652

Delectric withstanding Voltage in Volts: 200.0 Main Body Inside Diameter: 1.060 inches as supplied First Branch Inside Diameter: 0.520 inches as supplied Distance From Intersecting Centerline Of Main Body To End Of First Branch: 2.110 inches after unrestricted recovery Main Body Wall Thickness: 0.100 inches after unrestricted recovery First Branch Wall Thickness: 0.060 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 2.750 inches after unrestricted recovery Main Bodylength: 5.700 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1800 pounds per square inch Flexibility: Flexibile Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: — Demilitarization: No Flig: A22500	
Main Body Inside Diameter: 1.060 inches as supplied First Branch Inside Diameter: 0.520 inches as supplied Distance From Intersecting Centerline Of Main Body To End Of First Branch: 2.110 inches after unrestricted recovery Main Body Wall Thickness: 0.100 inches after unrestricted recovery First Branch Wall Thickness: 0.060 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 2.750 inches after unrestricted recovery Main Bodylength: 5.700 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1800 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Dielectric Withstanding Voltage In Volts:
1.060 inches as supplied First Branch Inside Diameter: 0.520 inches as supplied Distance From Intersecting Centerline Of Main Body To End Of First Branch: 2.110 inches after unrestricted recovery Main Body Wall Thickness: 0.100 inches after unrestricted recovery First Branch Wall Thickness: 0.060 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 2.750 inches after unrestricted recovery Main Bodylength: 5.700 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1800 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	
First Branch Inside Diameter: 0.520 inches as supplied Distance From Intersecting Centerline Of Main Body To End Of First Branch: 2.110 inches after unrestricted recovery Main Body Wall Thickness: 0.100 inches after unrestricted recovery First Branch Wall Thickness: 0.060 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 2.750 inches after unrestricted recovery Main Bodylength: 5.700 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1800 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	-
0.520 inches as supplied Distance From Intersecting Centerline Of Main Body To End Of First Branch: 2.110 inches after unrestricted recovery Main Body Wall Thickness: 0.100 inches after unrestricted recovery First Branch Wall Thickness: 0.060 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 2.750 inches after unrestricted recovery Main Bodylength: 5.700 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1800 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	• •
Distance From Intersecting Centerline Of Main Body To End Of First Branch: 2.110 inches after unrestricted recovery Main Body Wall Thickness: 0.100 inches after unrestricted recovery First Branch Wall Thickness: 0.060 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 2.750 inches after unrestricted recovery Main Bodylength: 5.700 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1800 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: — Demilitarization: No Flig:	First Branch Inside Diameter:
2.110 inches after unrestricted recovery Main Body Wall Thickness: 0.100 inches after unrestricted recovery First Branch Wall Thickness: 0.060 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 2.750 inches after unrestricted recovery Main Bodylength: 5.700 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1800 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Figg:	0.520 inches as supplied
Main Body Wall Thickness: 0.100 inches after unrestricted recovery First Branch Wall Thickness: 0.060 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 2.750 inches after unrestricted recovery Main Bodylength: 5.700 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1800 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: — Demilitarization: No Fitig:	Distance From Intersecting Centerline Of Main Body To End Of First Branch:
0.100 inches after unrestricted recovery First Branch Wall Thickness: 0.060 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 2.750 inches after unrestricted recovery Main Bodylength: 5.700 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1800 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	2.110 inches after unrestricted recovery
First Branch Wall Thickness: 0.060 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 2.750 inches after unrestricted recovery Main Bodylength: 5.700 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1800 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Flig:	Main Body Wall Thickness:
0.060 inches after unrestricted recovery Distance From Edge Of Main Body To Intersecting Centerlines: 2.750 inches after unrestricted recovery Main Bodylength: 5.700 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1800 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Filig:	0.100 inches after unrestricted recovery
Distance From Edge Of Main Body To Intersecting Centerlines: 2.750 inches after unrestricted recovery Main Bodylength: 5.700 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1800 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	First Branch Wall Thickness:
2.750 inches after unrestricted recovery Main Bodylength: 5.700 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1800 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	0.060 inches after unrestricted recovery
Main Bodylength: 5.700 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1800 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Distance From Edge Of Main Body To Intersecting Centerlines:
5.700 inches after unrestricted recovery Angle Between Main Body And First Branch Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1800 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	2.750 inches after unrestricted recovery
Angle Between Main Body And First Branch Centerlines In Deg: 45.0 after unrestricted recovery Min. Tensile Strength (psi): 1800 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Main Bodylength:
45.0 after unrestricted recovery Min. Tensile Strength (psi): 1800 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	5.700 inches after unrestricted recovery
Min. Tensile Strength (psi): 1800 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Angle Between Main Body And First Branch Centerlines In Deg:
1800 pounds per square inch Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	45.0 after unrestricted recovery
Flexibility: Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Min. Tensile Strength (psi):
Flexible Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	1800 pounds per square inch
Color: Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Flexibility:
Black Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Flexible
Material: Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Color:
Rubber, synthetic Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Black
Material: Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Rubber synthetic Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Rubber, synthetic
Style Designator: Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material:
Transition-45 degrees Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Rubber synthetic
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:
N/a Unit Of Measure: Demilitarization: No Fiig:	Transition-45 degrees
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
Demilitarization: No Fiig:	N/a
No Fiig:	Unit Of Measure:
No Fiig:	_
Fiig:	Demilitarization:
-	No
-	Fiig:
	A22500