NSN 5970-01-036-3464

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-036-3464
Dielectric Withstanding Voltage In Volts:
200.0
Tempurature Rating:
-55.0 degrees celsius and 225.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant
Distance From Centerline Of Main Body To End Of First Branch:
2.140 inches after unrestricted recovery
Main Body Inside Diameter:
0.520 inches as supplied
First Branch Inside Diameter:
1.060 inches as supplied
Main Body Wall Thickness:
0.060 inches as supplied
First Branch Wall Thickness:
0.060 inches after unrestricted recovery
Main Bodylength:
2.640 inches after unrestricted recovery
Angle Between Main Body And First Branch Centerlines In Deg:
90.0 after unrestricted recovery
Heat Shrinkage Rating In Percent:
50.0
Min. Tensile Strength (psi):
1600 pounds per square inch
Flexibility:
Flexible
Color:
Black
Material:
Rubber, synthetic, rt-1312, raychem corp
Material:
Rubber, synthetic, rt-1312, raychem corp
Style Designator:
Transition-t
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A22500