

View Online at <https://aerobasegroup.com/nsn/5970-01-036-3464>

Dielectric Withstanding Voltage In Volts:

200.0

Tempurature Rating:

-55.0 degrees celsius and 225.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant

Distance From Centerline Of Main Body To End Of First Branch:

2.140 inches after unrestricted recovery

Main Body Inside Diameter:

0.520 inches as supplied

First Branch Inside Diameter:

1.060 inches as supplied

Main Body Wall Thickness:

0.060 inches as supplied

First Branch Wall Thickness:

0.060 inches after unrestricted recovery

Main Bodylength:

2.640 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

90.0 after unrestricted recovery

Heat Shrinkage Rating In Percent:

50.0

Min. Tensile Strength (psi):

1600 pounds per square inch

Flexibility:

Flexible

Color:

Black

Material:

Rubber, synthetic, rt-1312, raychem corp

Material:

Rubber, synthetic, rt-1312, raychem corp

Style Designator:

Transition-t

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500