

View Online at <https://aerobasegroup.com/nsn/5970-01-036-5980>

**Dielectric Withstanding Voltage In Volts:**

200.0

**Tempurature Rating:**

-55.0 degrees celsius and 225.0 degrees celsius

**Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant

**Main Body Inside Diameter:**

0.520 inches as supplied

**First Branch Inside Diameter:**

0.260 inches as supplied

**Distance From Intersecting Centerline Of Main Body To End Of First Branch:**

0.840 inches after unrestricted recovery

**Main Body Wall Thickness:**

0.060 inches as supplied

**First Branch Wall Thickness:**

0.260 inches as supplied

**Distance From Edge Of Main Body To Intersecting Centerlines:**

0.900 inches after unrestricted recovery

**Main Bodylength:**

1.760 inches after unrestricted recovery

**Angle Between Main Body And First Branch Centerlines In Deg:**

45.0 after unrestricted recovery

**Heat Shrinkage Rating In Percent:**

50.0

**Min. Tensile Strength (psi):**

1200 pounds per square inch

**Flexibility:**

Flexible

**Color:**

Black

**Material:**

Rubber, synthetic, rt-1312, raychem corp

**Material:**

Rubber, synthetic, rt-1312, raychem corp

**Style Designator:**

Transition-45 degrees

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500