

View Online at <https://aerobasegroup.com/nsn/5970-01-041-3884>

Reliability Indicator:

Not established

Tempurature Rating:

-55.0 degrees celsius and 125.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Distance From Centerline Of Main Body To End Of First Branch:

1.160 inches after unrestricted recovery

Main Body Inside Diameter:

0.520 inches as supplied

First Branch Inside Diameter:

0.520 inches as supplied

Main Body Wall Thickness:

0.060 inches as supplied

First Branch Wall Thickness:

0.060 inches after unrestricted recovery

Main Bodylength:

2.310 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

90.0 after unrestricted recovery

Min. Tensile Strength (psi):

1200 pounds per square inch

Flexibility:

Flexible

Color:

Black

Material:

Plastic, pololefin, rt-1304, raychem corp

Material:

Plastic, pololefin, rt-1304, raychem corp

Style Designator:

Transition-t

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500