Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-045-8998

| view Online at https://aerobasegroup.com/nsn/5970-01-045-8998 | |
|--|--|
| Tempurature Rating: | |
| -55.0 degrees celsius and 135.0 degrees celsius | |
| Environmental Protection: | |
| Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant | |
| Main Body Wall Thickness: | |
| 0.100 inches after unrestricted recovery | |
| Main Bodylength: | |
| 2.550 inches after unrestricted recovery | |
| Main Body Small End Inside Diameter: | |
| 0.670 inches as supplied | |
| Main Body Large End Inside Diameter: | |
| 2.000 inches as supplied | |
| Distance From Bottom Of Shoulder To Large End Of Main Body: | |
| 1.460 inches after unrestricted recovery | |
| Distance From Top Of Shoulder To Small End Of Main Body: | |
| 0.500 inches after unrestricted recovery | |
| Min. Tensile Strength (psi): | |
| 1200 pounds per square inch | |
| Special Features: | |
| Wall thk tapers from large end of main body to 0.060 in. Small end | |
| Flexibility: | |
| Flexible | |
| Color: | |
| Black | |
| Material: | |
| Plastic, polyolefin, rt-1304, raychem corp | |
| Material: | |
| Plastic, polyolefin, rt-1304, raychem corp | |
| Style Designator: | |
| Boot-straight | |
| Dielectric Material Voltage Rating Per Unit Thickness: | |
| 200.0 volts per military /0.001 inch/ | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Filg: | |
| A22500 | |
| | |