Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-046-1316

| Tempurature Rating:  |
|--|
| -55.0 degrees celsius and 135.0 degrees celsius  |
| Environmental Protection:  |
| Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant   |
| Main Body Wall Thickness:  |
| 0.080 inches after unrestricted recovery   |
| Main Bodylength:   |
| 3.900 inches after unrestricted recovery   |
| Main Body Small End Inside Diameter:   |
| 1.050 inches as supplied   |
| Main Body Large End Inside Diameter:   |
| 3.000 inches as supplied   |
| Distance From Bottom Of Shoulder To Large End Of Main Body:  |
| 2.470 inches after unrestricted recovery   |
| Distance From Top Of Shoulder To Small End Of Main Body:   |
| 0.990 inches after unrestricted recovery   |
| Min. Tensile Strength (psi):   |
| 1200 pounds per square inch  |
| Flexibility:   |
| Flexible   |
| Color:   |
| Black  |
| Material:  |
| Plastic, polyolefin, rt-1304, raychem corp   |
| Material:  |
| Plastic, polyolefin, rt-1304, raychem corp   |
| Style Designator:  |
| Boot-straight  |
| Dielectric Material Voltage Rating Per Unit Thickness:   |
| 200.0 volts per military /0.001 inch/  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| -  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A22500   |
| Dielectric Material Voltage Rating Per Unit Thickness:<br>200.0 volts per military /0.001 inch/<br>Shelf Life:<br>N/a<br>Unit Of Measure:<br><br>Demilitarization:<br>No<br>Fig: |