

View Online at <https://aerobasegroup.com/nsn/5970-01-050-9761>

**Temperature Rating:**

-55.0 degrees celsius

**Environmental Protection:**

Corrosion resistant and mildew resistant and solvent resistant and water resistant

**Main Body Inside Diameter:**

2.050 inches as supplied

**First Branch Inside Diameter:**

0.800 inches as supplied

**Second Branch Inside Diameter:**

0.800 inches as supplied

**Third Branch Inside Diameter:**

0.800 inches as supplied

**Fourth Branch Inside Diameter:**

0.800 inches as supplied

**Main Body Wall Thickness:**

0.100 inches after unrestricted recovery

**First Branch Wall Thickness:**

0.100 inches after unrestricted recovery

**Second Branch Wall Thickness:**

0.100 inches after unrestricted recovery

**Third Branch Wall Thickness:**

0.100 inches after unrestricted recovery

**Fourth Branch Wall Thickness:**

0.100 inches after unrestricted recovery

**Main Bodylength:**

4.250 inches after unrestricted recovery

**Min. Tensile Strength (psi):**

1200 pounds per square inch

**Special Features:**

Inside surface coated with s-1017 adhesive

**Flexibility:**

Flexible

**Color:**

Black

**Material:**

Plastic, polyolefin, rt1304, raychem corp

**Material:**

Plastic, polyolefin, rt1304, raychem corp

**Dielectric Material Voltage Rating Per Unit Thickness:**

225.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500