NSN 5970-01-050-9761

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-050-9761

Tempurature Rating:

-55.0 degrees celsius

Environmental Protection:

Corrosion resistant and mildew resistant and solvent resistant and water resistant

Main Body Inside Diameter:

2.050 inches as supplied

First Branch Inside Diameter:

0.800 inches as supplied

Second Branch Inside Diameter:

0.800 inches as supplied

Third Branch Inside Diameter:

0.800 inches as supplied

Fourth Branch Inside Diameter:

0.800 inches as supplied

Main Body Wall Thickness:

0.100 inches after unrestricted recovery

First Branch Wall Thickness:

0.100 inches after unrestricted recovery

Second Branch Wall Thickness:

0.100 inches after unrestricted recovery

Third Branch Wall Thickness:

0.100 inches after unrestricted recovery

Fourth Branch Wall Thickness:

0.100 inches after unrestricted recovery

Main Bodylength:

4.250 inches after unrestricted recovery

Min. Tensile Strength (psi):

1200 pounds per square inch

Special Features:

Inside surface coated with s-1017 adhesive

Flexibility:

Flexible

Color:

Black

Material:

Plastic, polyolefin, rt1304, raychem corp

Material:

Plastic, polyolefin, rt1304, raychem corp

Dielectric Material Voltage Rating Per Unit Thickness:

225.0 volts per military /0.001 inch/

Shelf Life:

N/a

NSN 5970-01-050-9761

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A22500