

View Online at <https://aerobasegroup.com/nsn/5970-01-053-4176>

Tempurature Rating:

-55.0 degrees celsius and 135.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and water resistant

Main Body Inside Diameter:

1.060 inches as supplied

First Branch Inside Diameter:

0.520 inches as supplied

Second Branch Inside Diameter:

0.520 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

1.700 inches after unrestricted recovery

Main Body Wall Thickness:

0.100 inches after unrestricted recovery

First Branch Wall Thickness:

0.060 inches after unrestricted recovery

Second Branch Wall Thickness:

0.060 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

1.500 inches after unrestricted recovery

Angle Between Main Body And Second Branch Centerlines In Deg:

22.5 after unrestricted recovery

Min. Tensile Strength (psi):

1200 pounds per square inch

Flexibility:

Flexible

Color:

Black

Material:

Plastic, polyolefin, rt1304, raychem corp

Material:

Plastic, polyolefin, rt1304, raychem corp

Style Designator:

Transition-y

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500