
Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-053-5137

Tempurature Rating:
-55.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Main Body Inside Diameter:
2.050 inches as supplied
First Branch Inside Diameter:
0.800 inches as supplied
Second Branch Inside Diameter:
0.800 inches as supplied
Third Branch Inside Diameter:
0.800 inches as supplied
Fourth Branch Inside Diameter:
0.800 inches as supplied
Main Body Wall Thickness:
0.100 inches after unrestricted recovery
First Branch Wall Thickness:
0.100 inches after unrestricted recovery
Second Branch Wall Thickness:
0.100 inches after unrestricted recovery
Third Branch Wall Thickness:
0.100 inches after unrestricted recovery
Fourth Branch Wall Thickness:
0.100 inches after unrestricted recovery
Main Bodylength:
4.250 inches after unrestricted recovery
Min. Tensile Strength (psi):
1500 pounds per square inch
Flexibility:
Semirigid
Color:
Black
Material:
Plastic, polyolefin, rt-301, raychem corp
Material:
Plastic, polyolefin, rt-301, raychem corp
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500