## NSN 5970-01-053-5138

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-053-5138

## **Tempurature Rating:**

121.0 degrees celsius

#### **Environmental Protection:**

Flame resistant and mildew resistant and solvent resistant and water resistant

#### Large End Wall Thickness Of Main Body:

1.5 millimeters after unrestricted recovery

#### Small End Wall Thickness Of Main Body:

0.8 millimeters after unrestricted recovery

#### Distance From Intersecting Centerlines To Edge Of Small End:

32.0 millimeters after unrestricted recovery

#### Distance From Centerline Of Small End To Edge Of Large End:

20.0 millimeters after unrestricted recovery

#### Main Body Small End Inside Diameter:

6.6 millimeters after unrestricted recovery

#### Main Body Large End Inside Diameter:

28.5 millimeters as supplied

#### Distance From Top Of Shoulder To Small End Of Main Body:

12.0 millimeters after unrestricted recovery

#### Angle Between Large End And Small End Centerlines In Deg:

90.0 as supplied

## **Heat Shrinkage Rating In Percent:**

50.0

#### Min. Tensile Strength (psi):

1500 pounds per square inch

## Flexibility:

Semirigid

## Height:

27.2 millimeters after unrestricted recovery

#### Color:

Black

#### Material:

Plastic, polyolefin, rt-301, raychem corp

## Material:

Plastic, polyolefin, rt-301, raychem corp

#### **Style Designator:**

Boot-90 degrees

## **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5970-01-053-5138

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500