NSN 5970-01-065-2871

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-065-2871

Tom	nuratur	e Rating	
ı em	puratur	e Kating	-

-55.0 degrees celsius and 300.0 degrees celsius

Environmental Protection:

Flame resistant and mildew resistant and solvent resistant and water resistant

Main Body Wall Thickness:

0.070 inches after unrestricted recovery

Main Bodylength:

2.920 inches after unrestricted recovery

Main Body Small End Inside Diameter:

0.220 inches as supplied

Main Body Large End Inside Diameter:

1.030 inches as supplied

Distance From Bottom Of Shoulder To Large End Of Main Body:

0.480 inches after unrestricted recovery

Min. Tensile Strength (psi):

1800 pounds per square inch

Special Features:

Includes 2 drain holes; large end has lip; small end wall thickness 0.045 in.

Flexibility:

Flexible

Color:

Black

Material:

Rubber, rt-1312/thermofit viton/raychem corp

Material:

Rubber, rt-1312/thermofit viton/raychem corp

Style Designator:

Boot-straight-long

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A22500