NSN 5970-01-066-1540

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-066-1540

Tempurature Rating:

-55.0 degrees celsius and 200.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and water resistant

Large End Wall Thickness Of Main Body:

0.080 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.045 inches after unrestricted recovery

Main Bodylength:

8.410 inches after unrestricted recovery

Main Body Small End Inside Diameter:

1.070 inches as supplied

Main Body Large End Inside Diameter:

1.720 inches as supplied

Distance From Top Of Shoulder To Small End Of Main Body:

6.660 inches after unrestricted recovery

End Largest Diameter:

1.532 inches after unrestricted recovery

Min. Tensile Strength (psi):

1800 pounds per square inch

Lip Height:

0.120 inches after unrestricted recovery

Lip Width:

0.065 inches after unrestricted recovery

Special Features:

Yellow color stripe; 4 drain holes included

Flexibility:

Flexible

Height:

1.080 inches after unrestricted recovery

Color:

Black

Material:

Plastic, fluoroelastomer, mil-i-81765/4

Material:

Plastic, fluoroelastomer, mil-i-81765/4

Style Designator:

Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

NSN 5970-01-066-1540

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A22500