NSN 5970-01-066-3962

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-066-3962

Environmental Protection:

Flame resistant and mildew resistant and water resistant

Large End Wall Thickness Of Main Body:

0.070 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.045 inches after unrestricted recovery

Main Bodylength:

2.650 inches after unrestricted recovery

Main Body Small End Inside Diameter:

0.220 inches as supplied

Main Body Large End Inside Diameter:

0.670 inches after unrestricted recovery

Distance From Top Of Shoulder To Small End Of Main Body:

1.150 inches after unrestricted recovery

End Largest Diameter:

0.890 inches after unrestricted recovery

Min. Tensile Strength (psi):

1200 pounds per square inch

Lip Height:

0.120 inches after unrestricted recovery

Lip Width:

0.040 inches after unrestricted recovery

Special Features:

Drain holes included

Flexibility:

Flexible

Height:

0.710 inches after unrestricted recovery

Color:

Black

Material:

Rubber, viton, rt-1312, raychem corp

Material:

Rubber, viton, rt-1312, raychem corp

Style Designator:

Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5970-01-066-3962

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



em			

No

Fiig:

A22500