Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-067-4788

Tempurature Rating: 220.0 degrees celsius Environmental Protection: Solvent resistant Expanded Inside Diameter: 0.500 inches Recovered Inside Diameter: 0.250 inches Recovered Wall Thickness: 0.260 inches Heat Shrinkage Rating In Percent: 50.0 9.0 Win Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexibility: Flexibility: Flexibility: Solve resignator: Style Designator: Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 150.0 volts per military /0.001 inch/ Sheir Life: Na Unit Of Measure: * * Penilitarization: Na Stig: Stig: <th></th>	
Environmental Protection: Solvent resistant Expanded Inside Diameter: 0.500 inches Recovered Inside Diameter: 0.250 inches Recovered Mall Thickness: 0.048 inches Heat Shrinkage Rating In Percent: 50.0 Solo pounds per square inch Flexibility: Store Na Co	
Solvent resistant Expanded Inside Diameter: 0.500 inches Recovered Inside Diameter: 0.250 inches Recovered Wall Thickness: 0.048 inches Heat Shrinkage Rating In Percent: 5.00 5.00 Min Tensile Strength (psi): 1500 pounds per square inch Flexibility: Subder synthetic Style Designator: Style	-
Expanded Inside Diameter: 0.500 inches Recovered Inside Diameter: 0.250 inches Recovered Wall Thickness: 0.048 inches Betabrinkage Rating In Percent: 50.0 Min Ensile Strength (psi): 1500 pounds per square inch Heixbilty: Flexibilty: Rober square inch Mintersile Otor: Black Material: Rubber synthetic Style Designator: Shrinkable Delectric Material Voltage Rating Per Unit Thickness: 1500 volts per military /0.001 inch/ Sheff Life: Na Material: It of Messure:	Environmental Protection:
0.500 inches Recovered Inside Diameter: 0.250 inches Recovered Wall Thickness: 0.048 inches Heat Shrinkage Rating In Percent: 50.0 Min. Tonsile Strength (psi): 1500 pounds per square inch Flexibility: Flexibility: Robert Black Material: Rubber synthetic Style Designator: 150.0 volts per military/0.001 inch/ Sheff Life: Na Naterial: 150.0 volts per military/0.001 inch/ Sheff Life: Na Sheff Life: Na Field Material Voltage Rating Per Unit Thickness: 150.0 volts per military/0.001 inch/ Sheff Life: Na Lift of Measure: Image: Na Sheff Life: Na Sheff Life: Na Sheff Life: Sheff Life: Sheff Life: Sheff Life: Sheff Life: S	Solvent resistant
Recovered Inside Diameter: 0.250 inches Recovered Wall Thickness: 0.048 inches Heat Shrinkage Rating In Percent: 50.0 Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexibility: Flexibility: Black Color: Black Material: Rubber synthetic Style Designator: Sto.0 volts per military /0.001 inch/ Sheff Life: Na Chif Measure: - Provet Chif Measure: - Provet Chif Measure: - Fig: Fig:	Expanded Inside Diameter:
0.250 inches Recovered Wall Thickness: 0.048 inches Bet Shrinkage Rating In Percent: Solo Min. Tensile Strength (psi): 1500 pounds per square inch Fexibility:	0.500 inches
Recovered Wall Thickness: 0.048 inches Hat Shrinkage Rating In Percent: 50.0 Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexibility: Flexibility: Rober synthetic Back Material: Rubber synthetic Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 150.0 volts per military /0.001 inch/ Sheff Life: Na Material: Na Dielectric Material Voltage Rating Per Unit Thickness: 150.0 volts per military /0.001 inch/ Sheff Life: Na Dielectric Material Voltage Rating Per Unit Thickness: Na	Recovered Inside Diameter:
0.498 inchesHeat Shrinkage Rating In Percent:50.0Min. Tensile Strength (psi):1500 pounds per square inchFlexibility:Flexibility:FlexibleColor:BlackMaterial:Ruber syntheticStyle Designator:ShrinkableDelectric Material Voltage Rating Per Unit Thickness:150.0 volts per military /0.001 inch/Sheff Life:NaInt Of Measure:-Denlitarization:NaFig:Fig:	0.250 inches
Heat Shrinkage Rating In Percent:50.0Min. Tensile Strength (psi):1500 pounds per square inchFlexibiliy:Flexibiliy:FlexibleColor:BlackMaterial:Ruber syntheticStyle Designator:ShrinkableDelectric Material Voltage Rating Per Unit Thickness:150.0 volts per military /0.001 inch/Sheff Life:N/aInt Of Measure:-Delicting Calification:NoFig:Fig:	Recovered Wall Thickness:
50.0Min. Tensile Strength (psi):1500 pounds per square inchFlexibility:Flexibility:FlexibleColor:BlackMaterial:Rubber syntheticStyle Designator:ShrinkableDielectric Material Voltage Rating Per Unit Thickness:150.0 volts per military /0.001 inch/Shelf Life:NaDielectric Material Voltage Rating Per Unit Thickness:150.0 volts per military /0.001 inch/Shelf Life:NaDielectric Material Notage Rating Per Unit Thickness:NaFig:NaShelf Life:NaShelf Life:Shelf Life: <tr< th=""><th>0.048 inches</th></tr<>	0.048 inches
Min. Tensile Strength (psi): 1500 pounds per square inch Flexibility: Flexibile Flexible Color: Black Material: Rubber synthetic Style Designator: Shrinkable Delectric Material Voltage Rating Per Unit Thickness: 150.0 volts per military /0.001 inch/ Sheft Life: N/a Endersen: Int of Measure: Penilitarization: No Fig:	Heat Shrinkage Rating In Percent:
1500 pounds per square inchFlexibility:FlexibleFlexibleColor:BlackMaterial:Rubber syntheticStyle Designator:ShrinkableDelectric Material Voltage Rating Per Unit Thickness:150.0 volts per military /0.001 inch/Shelf Life:N/aUnit Of Measure:-Penilitarization:NoFig:	50.0
Flexibility:Flexibility:FlexibileFlexibileColor:BlackBlackMaterial:Rubber syntheticStyle Designator:ShrinkableDelectric Material Voltage Rating Per Unit Thickness:150.0 volts per military /0.001 inch/Sheff Life:N/aUnit Of Measure:-Penilitarization:NoFig:	Min. Tensile Strength (psi):
FlexibleColor:BlackBterial:Rubber syntheticStyle Designator:ShrinkableDelectric Material Voltage Rating Per Unit Thickness:150.0 volts per military /0.001 inch/Shelf Life:N/aUnit Of Measure:Penilitarization:NoFig:	1500 pounds per square inch
Color:BlackMaterial:Rubber syntheticStyle Designator:ShrinkableDelectric Material Voltage Rating Per Unit Thickness:150.0 volts per military /0.001 inch/Shelf Life:N/aUnit Of Measure:Penilitarization:NoFig:	Flexibility:
BlackMaterial:Rubber syntheticRubber syntheticStyle Designator:ShrinkableDielectric Material Voltage Rating Per Unit Thickness:150.0 volts per military /0.001 inch/Shelf Life:N/aUnit Of Measure:Penilitarization:NoFig:	Flexible
Material:Rubber syntheticRubber syntheticStyle Designator:ShrinkableDelectric Material Voltage Rating Per Unit Thickness:150.0 volts per military /0.001 inch/Shelf Life:N/aInti Of Measure:Denlitarization:NoFig:	Color:
Rubber synthetic Style Designator: Shrinkable Delectric Material Voltage Rating Per Unit Thickness: 150.0 volts per military /0.001 inch/ Shelf Life: N/a Duto of Measure: Demilitarization: No Fig:	Black
Style Designator:ShrinkableDielectric Material Voltage Rating Per Unit Thickness:150.0 volts per military /0.001 inch/Shelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Material:
Shrinkable Dielectric Material Voltage Rating Per Unit Thickness: 150.0 volts per military /0.001 inch/ Shelf Life: N/a Via Unit Of Measure: Demilitarization: No Fig:	Rubber synthetic
Dielectric Material Voltage Rating Per Unit Thickness: 150.0 volts per military /0.001 inch/ Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Style Designator:
150.0 volts per military /0.001 inch/ Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Shrinkable
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Dielectric Material Voltage Rating Per Unit Thickness:
N/a Unit Of Measure: Demilitarization: No Fiig:	150.0 volts per military /0.001 inch/
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:
 Demilitarization: No Filg:	N/a
Demilitarization: No Fiig:	Unit Of Measure:
No Fiig:	-
Fiig:	Demilitarization:
	No
A22500	Fiig:
	A22500