NSN 5970-01-069-2811

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-069-2811

Tempurature Rating:

-75.0 degrees celsius

Environmental Protection:

Flame resistant and mildew resistant and solvent resistant and water resistant

Main Body Inside Diameter:

0.520 inches as supplied

First Branch Inside Diameter:

0.260 inches as supplied

Second Branch Inside Diameter:

0.260 inches as supplied

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

0.760 inches after unrestricted recovery

Main Body Wall Thickness:

0.060 inches after unrestricted recovery

First Branch Wall Thickness:

0.040 inches after unrestricted recovery

Second Branch Wall Thickness:

0.040 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

0.880 inches after unrestricted recovery

Angle Between Main Body And Second Branch Centerlines In Deg:

22.5 after unrestricted recovery

Min. Tensile Strength (psi):

600 pounds per square inch

Flexibility:

Flexible

Color:

Black

Material:

Rubber, silicone, rt-602, raychem corp

Material:

Rubber, silicone, rt-602, raychem corp

Style Designator:

Transition-y

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5970-01-069-2811

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500