

View Online at <https://aerobasegroup.com/nsn/5970-01-071-8874>

Reliability Indicator:

Not established

Temperature Rating:

-55.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Main Body Wall Thickness:

0.080 inches after unrestricted recovery

Main Bodylength:

2.630 inches after unrestricted recovery

Main Body Small End Inside Diameter:

1.220 inches as supplied

Main Body Large End Inside Diameter:

1.220 inches as supplied

Distance From Bottom Of Shoulder To Large End Of Main Body:

1.390 inches after unrestricted recovery

Distance From Top Of Shoulder To Small End Of Main Body:

0.700 inches after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

Inside adhesive coated; large end has lip; inside diameter has lips

Flexibility:

Semirigid

Color:

Black

Material:

Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mpp-262, minnesota mining and mfg co

Material:

Plastic, polyolefin, rt-301, raychem corporation or plastic, polyolefin, mpp-262, minnesota mining and mfg co

Style Designator:

Boot-straight

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A22500