## NSN 5970-01-078-4034

Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-078-4034 **Reliability Indicator:** Not established **Overall Length:** Any acceptable **Tempurature Rating:** -14.0 degrees celsius and 105.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and oil resistant **Expanded Inside Diameter:** 0.650 inches **Recovered Inside Diameter:** Between 0.481 inches and 0.560 inches **Recovered Wall Thickness:** Between 0.023 inches and 0.032 inches **Heat Shrinkage Rating In Percent:** 26.0 Min. Tensile Strength (psi): 3120 pounds per square inch **Special Features:** Imprinted with scotchtite 105 degree symbol c Flexibility: Flexible Color: Black Material: Plastic, polyvinyl chloride, mil-i-631, type f, form u, subform ua, grade c, class 1 Material: Plastic polyvinyl chloride **Style Designator:** Shrinkable **Dielectric Material Voltage Rating Per Unit Thickness:** 800.0 volts per military /0.001 inch/ Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

Fiig:

A22500