Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-078-4034

Reliability Ind	dicator:
Not establishe	ed
Overall Leng	th:
Any acceptab	le
Tempurature	Rating:
·14.0 degrees	celsius and 105.0 degrees celsius
Environment	al Protection:
Corrosion res	istant and flame resistant and mildew resistant and oil resistant
Expanded In:	side Diameter:
0.650 inches	
Recovered In	side Diameter:
3etween 0.48	1 inches and 0.560 inches
Recovered W	/all Thickness:
3etween 0.02	3 inches and 0.032 inches
Heat Shrinka	ge Rating In Percent:
26.0	
Min. Tensile	Strength (psi):
3120 pounds	per square inch
Special Featu	Jres:
mprinted with	scotchtite 105 degree symbol c
Flexibility:	
Flexible	
Color:	
Black	
Material:	
⊃lastic, polyv	inyl chloride, mil-i-631, type f, form u, subform ua, grade c, class 1
Material:	
Plastic polyvir	ıyl chloride
Style Design	ator:
Shrinkable	
Dielectric Ma	terial Voltage Rating Per Unit Thickness:
300.0 volts pe	er military /0.001 inch/
Shelf Life:	
N/a	
Unit Of Meas	ure:
-	
Demilitarizati	ion:
No	
Fiig:	
A22500	