Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-079-1501

Tempurature Rating: -55.0 degrees celsius and 135.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and water resistant Large End Wall Thickness Of Main Body: 0.060 inches after unrestricted recovery Small End Wall Thickness Of Main Body: 0.045 inches after unrestricted recovery Main Bodylength: 4.880 inches after unrestricted recovery Main Body Small End Inside Diameter: 1.010 inches as supplied Main Body Large End Inside Diameter: 1.010 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: Any acceptable as supplied **End Largest Diameter:** 0.710 inches after unrestricted recovery Min. Tensile Strength (psi): 1200 pounds per square inch Lip Height: 0.120 inches after unrestricted recovery Lip Width: 0.040 inches after unrestricted recovery **Special Features:** Red color stripe; drain holes included Flexibility: Flexible Height: 0.780 inches after unrestricted recovery Color: Black Material: Plastic, polyolefin, mil-i-81765/1, type ii Material: Plastic, polyolefin, mil-i-81765/1, type ii **Style Designator:** Boot-90 degrees **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life:

N/a

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A22500