Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-081-3882

| view Online at https://aerobasegroup.com/nsi//3970-01-081-3062   |
|--|
| Tempurature Rating:  |
| -55.0 degrees celsius  |
| Environmental Protection:  |
| Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant |
| Main Body Wall Thickness:  |
| 0.060 inches after unrestricted recovery   |
| Main Bodylength:   |
| 2.380 inches after unrestricted recovery   |
| Main Body Small End Inside Diameter:   |
| 0.250 inches as supplied   |
| Main Body Large End Inside Diameter:   |
| 0.760 inches as supplied   |
| Distance From Bottom Of Shoulder To Large End Of Main Body:  |
| 0.460 inches after unrestricted recovery   |
| Min. Tensile Strength (psi):   |
| 1500 pounds per square inch  |
| Special Features:  |
| Inside adhesive coated; wall thk narrows to 0.045 at small end   |
| Flexibility:   |
| Semirigid  |
| Color:   |
| Black  |
| Material:  |
| Plastic, polyolefin, rt-301, raychem corp  |
| Material:  |
| Plastic, polyolefin, rt-301, raychem corp  |
| Style Designator:  |
| Boot-straight-long   |
| Dielectric Material Voltage Rating Per Unit Thickness:   |
| 200.0 volts per military /0.001 inch/  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A22500   |
|  |
|  |