NSN 5970-01-081-6284

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-081-6284

| Tompurature Pating |
|---|
| Tempurature Rating: |
| 100.0 degrees celsius Environmental Protection: |
| Flame resistant |
| |
| Main Body Wall Thickness: |
| 1.0 millimeters after unrestricted recovery |
| Main Bodylength: |
| 80.0 millimeters after unrestricted recovery |
| Main Body Small End Inside Diameter: |
| 8.4 millimeters after unrestricted recovery |
| Main Body Large End Inside Diameter: |
| 36.0 millimeters as supplied |
| Distance From Bottom Of Shoulder To Large End Of Main Body: |
| 42.2 millimeters after unrestricted recovery |
| Distance From Top Of Shoulder To Small End Of Main Body: |
| 20.0 millimeters after unrestricted recovery |
| Min. Tensile Strength (psi): |
| 1200 pounds per square inch |
| Flexibility: |
| Flexible |
| Color: |
| Black |
| Material: |
| Plastic, polyolefin, rt-1304, rayclad tubes inc |
| Material: |
| Plastic, polyolefin, rt-1304, rayclad tubes inc |
| Style Designator: |
| Boot-straight |
| Dielectric Material Voltage Rating Per Unit Thickness: |
| 200.0 volts per military /0.001 inch/ |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A22500 |
| |