Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-083-4248

Tempurature Rating: -55.0 degrees celsius and 135.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and water resistant Large End Wall Thickness Of Main Body: 0.070 inches after unrestricted recovery Small End Wall Thickness Of Main Body: 0.070 inches after unrestricted recovery **Distance From Intersecting Centerlines To Edge Of Small End:** Any acceptable as supplied Distance From Centerline Of Small End To Edge Of Large End: Any acceptable as supplied Main Body Small End Inside Diameter: 1.220 inches as supplied Main Body Large End Inside Diameter: 1.220 inches as supplied Distance From Top Of Shoulder To Small End Of Main Body: Any acceptable as supplied Angle Between Large End And Small End Centerlines In Deg: 90.0 after unrestricted recovery Min. Tensile Strength (psi): 1200 pounds per square inch **Special Features:** Red color stripe; inside adhesive coated; large end has lip Flexibility: Flexible Height: 1.220 inches after unrestricted recovery Color: Black Material: Plastic, polyolefin, mil-i-81765/1, type ii Material: Plastic, polyolefin, mil-i-81765/1, type ii Style Designator: Boot-90 degrees **Dielectric Material Voltage Rating Per Unit Thickness:** 200.0 volts per military /0.001 inch/ Shelf Life: N/a Unit Of Measure:

NSN 5970-01-083-4248

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500