Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-084-2597

Tempurature Rating:

-55.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

Distance From Centerline Of Main Body To End Of First Branch:

Any acceptable as supplied

Main Body Inside Diameter:

1.200 inches as supplied

First Branch Inside Diameter:

0.700 inches as supplied

Main Body Wall Thickness:

0.090 inches as supplied

First Branch Wall Thickness:

0.050 inches as supplied

Main Bodylength:

3.170 inches as supplied

Angle Between Main Body And First Branch Centerlines In Deg:

5.0 as supplied and 25.0 as supplied

Min. Tensile Strength (psi):

1200 pounds per square inch

Special Features:

Main body id 0.700 in. Min as supplied, 0.350 in. Maximum after unretricted recovery opposite end; wall thk rapers to 0.050 in. as supplied

Flexibility:

Flexible

Color:

Any acceptable

Material:

Plastic, polyolefin, rt-1304, raychem corp

Material:

Plastic, polyolefin, rt-1304, raychem corp

Style Designator:

Transition-t

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500