NSN 5970-01-084-2597

A22500

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-084-2597

Tempurature Rating:
-55.0 degrees celsius
Environmental Protection:
Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant
Distance From Centerline Of Main Body To End Of First Branch:
Any acceptable as supplied
Main Body Inside Diameter:
1.200 inches as supplied
First Branch Inside Diameter:
0.700 inches as supplied
Main Body Wall Thickness:
0.090 inches as supplied
First Branch Wall Thickness:
0.050 inches as supplied
Main Bodylength:
3.170 inches as supplied
Angle Between Main Body And First Branch Centerlines In Deg:
5.0 as supplied and 25.0 as supplied
Min. Tensile Strength (psi):
1200 pounds per square inch
Special Features:
Main body id 0.700 in. Min as supplied, 0.350 in. Maximum after unretricted recovery opposite end; wall thk rapers to 0.050 in. as supplied
Flexibility:
Flexible
Color:
Any acceptable
Material:
Plastic, polyolefin, rt-1304, raychem corp
Material:
Plastic, polyolefin, rt-1304, raychem corp
Style Designator:
Transition-t
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: