## NSN 5970-01-084-3594



Electrical Insulation Sleeving - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5970-01-084-3594 **Reliability Indicator:** Not established **Overall Length:** Any acceptable **Tempurature Rating:** -70.0 degrees celsius and 121.0 degrees celsius **Environmental Protection:** Corrosion resistant and flame resistant and mildew resistant and water resistant **Expanded Inside Diameter:** 0.625 inches **Recovered Inside Diameter:** 0.357 inches **Recovered Wall Thickness:** Between 0.037 inches and 0.067 inches **Heat Shrinkage Rating In Percent:** 42.9 **End Application:** Mrap - cougar cat1 a2; mrap - cougar cat2 a2 Min. Tensile Strength (psi): 1500 pounds per square inch **Special Features:** Rubber, polychloroprene, mil-dtl-23053/1, class 2 Flexibility: Flexible Color: Black Material: Rubber, polychloroprene, mil-dtl-23053/1, class 2 Style Designator: Shrinkable **Dielectric Material Voltage Rating Per Unit Thickness:** 300.0 volts per military /0.001 inch/ Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No Fiig: A22500