NSN 5970-01-084-4088

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-084-4088

Tempurature Rating:

-55.0 degrees celsius and 135.0 degrees celsius

Environmental Protection:

Corrosion resistant and flame resistant and mildew resistant and water resistant

Large End Wall Thickness Of Main Body:

0.070 inches after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.070 inches after unrestricted recovery

Distance From Intersecting Centerlines To Edge Of Small End:

Any acceptable after unrestricted recovery

Distance From Centerline Of Small End To Edge Of Large End:

Any acceptable after unrestricted recovery

Main Body Small End Inside Diameter:

1.220 inches as supplied

Main Body Large End Inside Diameter:

1.220 inches as supplied

Distance From Top Of Shoulder To Small End Of Main Body:

Any acceptable after unrestricted recovery

Angle Between Large End And Small End Centerlines In Deg:

90.0 after unrestricted recovery

Min. Tensile Strength (psi):

1500 pounds per square inch

Special Features:

White color stripe; large end has lip

Flexibility:

Semirigid

Height:

1.220 inches after unrestricted recovery

Color:

Black

Material:

Plastic, polyolefin, mil-i-81765/1, type i

Material:

Plastic, polyolefin, mil-i-81765/1, type i

Style Designator:

Boot-90 degrees

Dielectric Material Voltage Rating Per Unit Thickness:

200.0 volts per military /0.001 inch/

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5970-01-084-4088

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



em			

No

Fiig:

A22500