Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-087-4556

Reliability Indicator:   Not established   Tempurature Rating:   -55.0 degrees celsius and 135.0 degrees celsius   Environmental Protection:   Corrosion resistant and flame resistant and mildew resistant and water resistant   Main Body Wall Thickness:   0.100 inches after unrestricted recovery
Tempurature Rating: -55.0 degrees celsius and 135.0 degrees celsius Environmental Protection: Corrosion resistant and flame resistant and mildew resistant and water resistant Main Body Wall Thickness:
-55.0 degrees celsius and 135.0 degrees celsius Environmental Protection: Corrosion resistant and flame resistant and mildew resistant and water resistant Main Body Wall Thickness:
Environmental Protection: Corrosion resistant and flame resistant and mildew resistant and water resistant Main Body Wall Thickness:
Corrosion resistant and flame resistant and mildew resistant and water resistant Main Body Wall Thickness:
Main Body Wall Thickness:
-
0.100 inches after unrestricted recovery
Main Bodylength:
8.000 inches after unrestricted recovery
Main Body Small End Inside Diameter:
2.470 inches as supplied
Main Body Large End Inside Diameter:
2.470 inches as supplied
Distance From Bottom Of Shoulder To Large End Of Main Body:
0.630 inches after unrestricted recovery
Min. Tensile Strength (psi):
1200 pounds per square inch
Flexibility:
Flexible
Color:
Black
Material:
Plastic, polyolefin, mil-i-81765/1, type ii
Material:
Plastic, polyolefin, mil-i-81765/1, type ii
Style Designator:
Boot-straight-long
Dielectric Material Voltage Rating Per Unit Thickness:
200.0 volts per military /0.001 inch/
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A22500