# NSN 5970-01-088-2131

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-088-2131

# **Tempurature Rating:**

-55.0 degrees celsius

#### **Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

# Large End Wall Thickness Of Main Body:

0.070 inches after unrestricted recovery

#### Small End Wall Thickness Of Main Body:

0.045 inches after unrestricted recovery

#### Main Bodylength:

3.500 inches after unrestricted recovery

#### Main Body Small End Inside Diameter:

1.160 inches as supplied

#### Main Body Large End Inside Diameter:

1.160 inches as supplied

#### Distance From Top Of Shoulder To Small End Of Main Body:

2.750 inches after unrestricted recovery

#### **End Largest Diameter:**

0.750 inches after unrestricted recovery

# Min. Tensile Strength (psi):

1200 pounds per square inch

# Lip Height:

0.120 inches after unrestricted recovery

#### Lip Width:

0.040 inches after unrestricted recovery

#### Flexibility:

Flexible

# Height:

0.820 inches after unrestricted recovery

#### Color:

Black

#### Material:

Plastic, polyolefin, rt-1304, raychem corp

# Material:

Plastic, polyolefin, rt-1304, raychem corp

# **Style Designator:**

Boot-90 degrees

# **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

# Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5970-01-088-2131

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Demilitarization:

No

Fiig:

A22500