Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-090-0899

# Tempurature Rating:

-55.0 degrees celsius

# **Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

# Distance From Centerline Of Main Body To End Of First Branch:

1.026 inches after unrestricted recovery and 1.254 inches after unrestricted recovery

# Main Body Inside Diameter:

1.060 inches as supplied

## First Branch Inside Diameter:

0.260 inches as supplied

## Main Body Wall Thickness:

0.080 inches after unrestricted recovery and 0.100 inches after unrestricted recovery

## First Branch Wall Thickness:

0.032 inches after unrestricted recovery and 0.048 inches after unrestricted recovery

## Main Bodylength:

3.141 inches after unrestricted recovery and 3.839 inches after unrestricted recovery

# Angle Between Main Body And First Branch Centerlines In Deg:

85.5 after unrestricted recovery and 94.5 after unrestricted recovery

# Min. Tensile Strength (psi):

1200 pounds per square inch

# Flexibility:

Flexible

## Color:

Black

## Material:

Plastic, polyolefin, rt-1304, raychem corp

## Material:

Plastic, polyolefin, rt-1304, raychem corp

# Style Designator:

Transition-t

# **Dielectric Material Voltage Rating Per Unit Thickness:**

200.0 volts per military /0.001 inch/

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A22500