Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-095-4167

Reliab	ility Indicator:
Not es	tablished
Overa	II Length:
Any ac	cceptable
Temp	urature Rating:
-67.0 c	degrees celsius and 250.0 degrees celsius
Enviro	onmental Protection:
Corros	sion resistant and flame resistant and mildew resistant and water resistant
Expan	ided Inside Diameter:
0.110	inches
Recov	vered Inside Diameter:
0.063	inches
Recov	vered Wall Thickness:
Betwe	en 0.004 inches and 0.008 inches
Heat S	Shrinkage Rating In Percent:
42.7	
Min. T	ensile Strength (psi):
2500 p	bounds per square inch
Flexib	ility:
Flexibl	e
Color:	
Black	
Materi	ial:
Plastic	c, polytetrafluoroethylene, mil-i-23053/12, class 4
Materi	ial:
Plastic	polytetrafluoroethylene
Style	Designator:
Shrink	able
Dielec	tric Material Voltage Rating Per Unit Thickness:
800.0	volts per military /0.001 inch/
Shelf	Life:
N/a	
Unit C	of Measure:
 Demili	itarization:
No	
Fiig:	