Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-100-6390

| Dellekiliku Indiazian  |
|--|
| Reliability Indicator:                                       |
| Not established  |
| Overall Length:  |
| Any acceptable   |
| Tempurature Rating:  |
| -20.0 degrees celsius and 105.0 degrees celsius              |
| Environmental Protection:                                    |
| Corrosion resistant and mildew resistant and water resistant |
| Expanded Inside Diameter:                                    |
| 0.063 inches   |
| Recovered Inside Diameter:                                   |
| 0.031 inches   |
| Recovered Wall Thickness:                                    |
| Between 0.017 inches and 0.023 inches                        |
| Heat Shrinkage Rating In Percent:                            |
| 50.8   |
| Min. Tensile Strength (psi):                                 |
| 1800 pounds per square inch                                  |
| Flexibility:   |
| Flexible   |
| Color:   |
| Clear  |
| Material:  |
| Plastic, polyvinyl chloride, mil-i-23053/2, class 2          |
| Style Designator:  |
| Shrinkable   |
| Dielectric Material Voltage Rating Per Unit Thickness:       |
| 280.0 volts per military /0.001 inch/                        |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Νο   |
| Fiig:  |
| A22500   |
|  |
|  |