Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-101-2541

### Wall Thickness:

0.045 inches

**Reliability Indicator:** 

Not established

## Inside Diameter:

Between 1.500 inches and 1.550 inches

### **Overall Length:**

Any acceptable

#### **Tempurature Rating:**

-10.0 degrees celsius and 105.0 degrees celsius

### **Environmental Protection:**

Flame resistant and mildew resistant and oil resistant

#### Min. Tensile Strength (psi):

1800 pounds per square inch

#### Flexibility:

Flexible

# Color:

Black

### Material:

Plastic, polyvinyl chloride, mil-i-631, type f, form u, subform ua, grade c, class i, category i

## Material:

Plastic polyvinyl chloride

### Style Designator:

Nonshrinkable

### **Dielectric Material Voltage Rating Per Unit Thickness:**

475.0 volts per military /0.001 inch/

### **Specification Or Standard:**

I category and i class and u form and c grade and 1.500in. Size and ua subform and f type

### **Departure From Cited Document:**

As modified by color

#### Shelf Life:

N/a

# Unit Of Measure:

--

#### Demilitarization:

No

# Fiig:

A22500

### Mil-std (military Standard):

Mil-i-631 spec.