

View Online at <https://aerobasegroup.com/nsn/5970-01-101-9881>

**Tempurature Rating:**

-55.0 degrees celsius

**Environmental Protection:**

Corrosion resistant and flame resistant and mildew resistant and solvent resistant and water resistant

**Main Body Wall Thickness:**

0.070 inches after unrestricted recovery

**Main Bodylength:**

1.500 inches after unrestricted recovery

**Main Body Small End Inside Diameter:**

0.920 inches as supplied

**Main Body Large End Inside Diameter:**

0.920 inches as supplied

**Distance From Bottom Of Shoulder To Large End Of Main Body:**

0.830 inches after unrestricted recovery

**Distance From Top Of Shoulder To Small End Of Main Body:**

0.400 inches after unrestricted recovery

**Min. Tensile Strength (psi):**

1200 pounds per square inch

**Special Features:**

Large end has lip and circular ridge inside

**Flexibility:**

Flexible

**Color:**

Black

**Material:**

Plastic, polyolefin, rt-1304, raychem corporation or plastic, polyolefin, mpf-666, minnesota mining and mfg co

**Material:**

Plastic, polyolefin, rt-1304, raychem corporation or plastic, polyolefin, mpf-666, minnesota mining and mfg co

**Style Designator:**

Boot-straight

**Dielectric Material Voltage Rating Per Unit Thickness:**

225.0 volts per military /0.001 inch/

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A22500